
válvulasCT
Pol. Ind. Can Torrella. Ronda Shimizu, 2. Nave 4
08233 VACARISSES (Barcelona) SPAIN
Tel. +34 93 828 04 44 · Fax +34 93 828 04 50
comercial@valvulasct.com www.valvulasct.com


ARTICULO:
WR2445
Válvula de Retención a disco extremos roscados.
Disk Check valve, threaded ends.


Características
1. Válvula de retención a disco guiado. 2. Construcción en Ac. Inox. AISI 316. 3. Extremos roscados según DIN 259. 4. Soldadura a TIG sin aporte de material. 5. Presión de apertura Min. 0.025 Bar Max. 0.035 Bar. 6. Presión de trabajo máxima 16 Kg / cm2. 7. Temperatura de trabajo -20 ºC + 150 ºC.

Features
1. Guide Disk Check valve. *2. Made by Stainlees Steel AISI 316.* *3. Threaded ends according DIN 259.* *4. Welded joints made with TIG method without any additional material.* *5. Opening pressure Min. 0.025 Bar Max. 0.035 Bar.* *6. Max. Working pressure 16 Kg / cm2.* *7. Working temperature -20 ºC + 150 ºC.*












Nº	Denominación/Name	Material	Acabado Superficial/Surface Treatment
1	Terminal Roscado / Threaded ends	Acero Inox AISI 316 / SS 316	------
2	Cuerpo / Body	Acero Inox AISI 316 / SS 316	------
3	Disco / Disc	Acero Inox AISI 316 / SS 316	------
4	Buje guia / Guide Bush	Teflón / PTFE	------
5	Soporte Buje guia / Guide Bush Support	Acero Inox AISI 316 / SS 316	------
6	Resorte / Spring	Acero Inox AISI 316 / SS 316	------
7	Asiento / Seal ring	Viton	------

válvulasCT
Pol. Ind. Can Torrella. Ronda Shimizu, 2. Nave 4
08233 VACARISSES (Barcelona) SPAIN
Tel. +34 93 828 04 44 · Fax +34 93 828 04 50
comercial@valvulasct.com www.valvulasct.com









Nº	Denominación/Name	Material	Acabado Superficial/Surface Treatment
1	Terminal Roscado / Threaded ends	Acero Inox AISI 316 / SS 316	------
2	Cuerpo / Body	Acero Inox AISI 316 / SS 316	------
3	Buje guia / Guide Bush	Teflón / PTFE	------
4	Soporte Buje guia / Guide Bush Support	Acero Inox AISI 316 / SS 316	------
5	Terminal Roscado / Threaded ends	Acero Inox AISI 316 / SS 316	------
6	Resorte / Spring	Acero Inox AISI 316 / SS 316	------
7	Disco / Disc	Acero Inox AISI 316 / SS 316	------
8	Alojamiento de Asiento / Seal ring Housing	Acero Inox AISI 316 / SS 316	------
9	Asiento / Seal ring	Viton	------
10	Anillo de asiento / Seal Ring retainer	Acero Inox AISI 316 / SS 316	------
11	Soporte de Asiento / Seal ring Support	Acero Inox AISI 316 / SS 316	------
12	Guia Inferior / Outlet side guide	Acero Inox AISI 316 / SS 316	------

válvulasCT
Pol. Ind. Can Torrella. Ronda Shimizu, 2. Nave 4
08233 VACARISSES (Barcelona) SPAIN
Tel. +34 93 828 04 44 · Fax +34 93 828 04 50
comercial@valvulasct.com www.valvulasct.com

DIMENSIONES GENERALES / GENERAL DIMENSIONS

Ref	Medida/Size	PN	Dimensiones/Dimensions (mm)			Peso/Weight (Kg)
			A	B	C	
WR244502	1/4"	16	20	55	32	0.094
WR244503	3/8"	16	20	55	32	0.091
WR244504	1/2"	16	25	55	32	0.930
WR244505	3/4"	16	29	70	44	0.129
WR244506	1	16	36	84	53	0.191
WR244507	1 1/4"	16	45	99	62	0.281
WR244508	1 1/2"	16	51	119	78	0.388
WR244509	2	16	64	123	89	0.704
WR244510	2 1/2"	16	80	147	113	1.425
WR244511	3	16	93	166	132	2.085
WR244512	4	16	120	193	167	3.415

DIAGRAMA DE PERDIDAS DE CARGA / HEAD LOSSES DIAGRAM

